



GENERAL PRODUCT SPECIFICATION

Item No.	AD30100-BLUE
-----------------	---------------------

Date	3-1-2017	Replaces		No. Pages	1
-------------	----------	-----------------	--	------------------	---

Product Description:

Style	Roll
Item Size (each)	30" x 100'
Color	Gray with Black Film Backing with Adhesive
Composition	96-98% Polypropylene + 2-4% EMA
Structure	A nonwoven mat comprised of staple fibers [25-35 micron diameters] with a co-extruded chemical resistant layer with a non-skid barrier backing along with adhesive. ** The bottom layer is non-skid but not chemical resistant. The rug must be applied to a clean surface.
Technology	Needlepunch + Co-extruded backing
Absorbency	Universal (Hydrophilic + Oleophilic)
Bonding	Mechanical needling entanglement + heat fused on 1-side + co-extrusion

Intended Application	Chemical Resistant Non-Skid Industrial Rug with Barrier properties for Water, Oil, or Solvent Base Liquids, with static resistant qualities.
-----------------------------	--

Absorbency Capacity	21 gal. per bale (saturated; medium viscosity-8x)
----------------------------	---

Packaging Description:

Package configuration	Case	Pkg. Weight	29-lbs
Items per Package	1-Roll/Box	Pkg. Dimensions	17" x 17" x 31" H
Container type	Catron		

Physical Properties:

<u>Parameter</u>	<u>SPC Test Method</u>	<u>Units</u>	<u>Nominal</u>	<u>(+/-)Tolerance</u>
Basis Weight	SPCTM-002A	G/M ²	420	40
Caliper	SPCTM-003A	mils	120	10
Absorbency** (med. Oil)	SPCTM-004B	gL/gS	8	1
Tear Strength	SPCTM-006	lbs	>100	>100
Color	Visual	-----	Blue	per standard

The above properties are “nominal” values used for **PROCESS CONTROL** when the product is produced and/or inspected. Performance “nominals” may vary depending upon the specific application, and/or the environment being applied, stored, or shipped.

** The "Absorbency" Spec and "SPCTM004" test method is based on the protocol of ASTM F726, using SAE20 non-detergent as the Oil Type, medium viscosity.

Attributes	Product will be free of foreign material contamination, rips, holes, and tears.
Labeling	Each package to be clearly labeled with Company Name, Address, Item No., Date, and/or Package Code (Bar Code).
Certification	Make no changes in basic process or composition without notifying customer. Claims for non-conformance of goods must be made within 60-days of delivery.